



LigoDLB 5-15ac-TH

5 GHz high-capacity wireless device

500 + Mbps


Incredible performance

500+ Mbps throughput - a result of powerful hardware platform with 802.11ac technology based radio and a proprietary data transmission protocol (iPoll). Based on a QCA 9563 CPU (750 MHz), QCA 9882 radio and 64 MBytes of RAM and 16 MBytes of flash memory the, LigoDLB 5-15 ac-TH series devices are an ideal solution for capacity demanding applications. State of the art RF design with great output power and sensitivity parameters improve range and capacity over highest modulation - 256 QAM. The 24V Gigabit Ethernet port (passive PoE) allows utilizing the full capacity of the radio when using in a point-to-point and point-to-multipoint scenario. LigoDLB ac series devices are backwards compatible with LigoDLB devices using iPoll mode, which helps to expand or upgrade existing networks using the latest technologies gradually.



New form factor

New shape of the enclosure is smaller, lighter and with retained IP-65 weather protection rating. Smaller packaging allows saving freight cost when shipping the goods. The new design has no metal parts, which makes the device lighter and corrosion resistant.



Powerfull OS

The DLB OS is a highly functional and easy to use operating system flawless operation of all DLB hardware devices and effortless setup for those deploying the networks. High performance (500 Mbps) allows offering more bandwidth together with additional services like VoIP and IPTV using a smart QoS mechanism and multicast traffic enhancements for tripple play services, which essential for all next generation service providers complementing their portfolio with more performance and reliability requiring services. iPoll - proprietary transmission protocol ensures smooth performance with a high number of clients even in a noisy environments.

Specifications

Distance recommendation	PTMP mode	PTP mode
LigoDLB 5-15 ac-TH	5 km/ 3.11 mi	7 km/ 4.35 mi

Wireless

WLAN standard	IEEE 802.11 a/n/ac, iPoll 3
Radio mode	MIMO 2x2
Radio frequency band	5 GHz models: 5.150 - 5.850 GHz (FCC 5.150 - 5.250 and 5.725 - 5.850 GHz)
Transmit power	Up to 15 dBm (For Thailand)
Channel size	5, 10, 20, 40, 80 MHz
Modulation schemes	802.11 a/n: OFDM (64-QAM, 16-QAM, QPSK, BPSK) 802.11 ac: OFDM (256-QAM, 64-QAM, 16-QAM, QPSK, BPSK)
Data rates	802.11 ac @ 40 MHz: 400, 360, 300, 270, 240, 180, 120, 90, 60, 30 Mbps 802.11 ac @ 80 MHz: 866, 780, 650, 585, 520, 390, 260, 195, 130, 65 Mbps
Error correction	FEC, LDPC
Duplexing scheme	Time division duplex

40 MHz	Modulation, Mbps	400	360	300	270	240	180	120	90	60	30
	TX Power, dBm	11	12	13	14	15	15	15	15	15	15
	Receive sensitivity, dBm	-70	-72	-76	-78	-80	-84	-87	-92	-94	-95
80 MHz	Modulation, Mbps	866	780	650	585	520	390	260	195	130	65
	TX Power, dBm	9	10	10	11	12	13	13	14	14	14
	Receive sensitivity, dBm	-64	-66	-70	-72	-74	-78	-81	-85	-88	-90

Antenna

Type	Integrated dual-polarized directional panel antenna
Gain	15 dBi

Wired

Interface	10/100/1000 Base-T, RJ45
-----------	--------------------------

Physical

Dimensions	158 mm (6.2"), 97 mm (3.8"), 38 mm (1.5")
Weight	185 g (0.4 lb)
Mounting	Pole mounting bracket included

Power

Power supply	24 VDC passive PoE (AC to 24 VDC adapter is included in the package)
Power source	100 – 240 VAC
Power consumption (max)	10 W

Environmental

Operating temperature	-40°C (-40 F) ~ +65°C (+149 F)
Humidity	0 ~ 90 % (non-condensing)


Management

System monitoring	SNMP, Syslog, Web UI, WNMS
Configuration	WebUI, WNMS

Regulatory

Certification	FCC/IC/CE
---------------	-----------

Antenna specifications



Frequency range	5.1 - 5.9 GHz
Gain	15 dBi
Polarization	Dual linear
Cross-pol Isolation	21 dBi
VSWR	<1.4
Azimuth beamwidth (H pol)	35 deg
Azimuth beamwidth (V pol)	35 deg
Elevation beamwidth	35 deg



LigoWave

www.ligowave.com

LigoDLB 5-15 ac-TH